



WWW.SEND0.GR



HERMES GOLD

NOTHING ELSE MATTERS BUT SUPREMACY



R32



INVERTER



Wi-Fi



GOLDEN FIN



IONIZER (Health mode)



PM. 2.5

← extra filters →



SILVER ION



Low operating voltage range 130 ~ 270V



4D air flow

Balanced airflow with range up to 18m and more precise temperature regulation.



Soundless design

A large compressor in conjunction with the best heat exchange system ensures better cooling performance.

B



Auto defrost

A



Self-diagnosis of faults

S



Sleep mode

I



Turbo mode

C



Auto restart

M



Timer

O



Antibacterial function

D



Self-cleaning function

E



Air flow up and down

S



Follow me mode

Model				SND - 09 HRS	SND - 12 HRS	SND - 18 HRS	SND - 24 HRS
Nameplate parameter	Rated capacity	Cooling	W	2600 (980 - 2900)	3550 (1100 - 3700)	5300 (1200 - 5500)	7100 (1970 - 7800)
		Heating	W	2700 (680 - 3000)	3500 (1100 - 3800)	5400 (1370 - 6100)	7050 (2500 - 7600)
	Rated power consumption	Cooling	W	800 (300 - 900)	1090 (340 - 1150)	1650 (370 - 2000)	2200 (600 - 2400)
		Heating	W	750 (190 - 830)	970 (300 - 1060)	1490 (350 - 1700)	1960 (700 - 2100)
	Rated running current	Cooling	A	3,6 (1,3 - 4,5)	4,8 (1,5 - 5,4)	7,3 (1,7 - 9,3)	10,3 (2,5 - 11)
		Heating	A	3,4 (0,9 - 4,0)	4,3 (1,3 - 5,0)	7,1 (1,6 - 8,0)	10,5 (2,4 - 10)
	Max. input power		W	1600	1900	2900	3700
	Max. input current		A	8	9,5	12	16
	SEER cooling		W/W	6,1 / A+++	6,1 / A+++	6,1 / A+++	6,1 / A+++
	SCOP heating		W/W	4,0 / A+++	4,0 / A+++	4,0 / A+++	4,0 / A+++
	Power supply source		V / Ph / Hz	220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz	220~240V-1-50Hz
	Refrigerant			R32	R32	R32	R32
	Refrigerant charged		g	580	680	1280	1440
	Air flow volume		m ³ / h	650	650	900	1250
	Sound power level	Indoor unit (Hi. / Med. / Lo.)	dB (A)	20 / 33 / 38	22 / 33 / 42	24 / 36 / 46	26 / 36 / 48
Outdoor unit		dB (A)	42	46	48	53	
Indoor unit weight		Kg	8	8,5	11	16	
Outdoor unit weight		Kg	26	26	35	45	
Piping size	Liquid	mm (inch)	1/4	1/4	1/4	1/4	
	Gas	mm (inch)	3/8	3/8	1/2	5/8	
Indoor unit configuration	Dimension	Net dimension (W x D x H)	mm	792 x 201 x 292	792 x 201 x 292	940 x 224 x 316	1132 x 232 x 330
Outdoor unit configuration	Dimension	Net dimension (W x D x H)	mm	730 x 285 x 545	730 x 285 x 545	800 x 315 x 545	900 x 350 x 700
Operation temperature	Operating range (cooling)	°C	16 - 43	16 - 43	16 - 43	16 - 43	
	Operating range (heating)	°C	-10 - 30	-10 - 30	-10 - 30	-10 - 30	

The company reserves the right to change the technical characteristics without notice.