

MULTI SPLIT

Indoor units *AEOLOS*




Wi-Fi



R32



INVERTER



EXTRA FILTERS



GOLDEN
FIN



FINISH
MATT



Remote control



Model	Internal unit		SFM-09ALSI-AU1	SFM-12ALSI-AU1	SFM-18ALSI-AU1
Rated Capacity	Cooling	Btu/h	9000(4780-11260)	12285(5800-12625)	17747(8530-19790)
		kW	2.58(1.40-3.30)	3.50(1.70-3.70)	5.27(2.50-5.80)
	Heating	Btu/h	9215(4095-10240)	12625(5120-12625)	18085(7680-19790)
		kW	2.70(1.20-3.00)	3.50(1.50-3.70)	5.37(2.25-5.80)
Electrical absorption	Power Supply Source	V~,Hz,Ph	220~240,50,1	220~240,50,1	220~240,50,1
	Absorption in cooling	W	40(12~68)	40(12~68)	63(16~88)
	Absorption in heating	W	40(12~68)	40(12~68)	63(16~88)
Fan motor	Power	W	12	12	30
	Speed (high / medium / low)	r/min	1150	1150	1330
Performance	Air Flow Volume	m ³ /h	600	600	850
	Sound Pressure Level	dB(A)	40/38/34	42/40/37	45/42/37
	Sound Power	dB(A)	54	52	55
Dimension	Net size (LxPxH)	mm	792x201x292	792x201x292	940x224x316
	Package dimensions (LxPxH)	mm	888x290x370	888x290x370	1010x310x385
Weight	Net	kg	8	8,5	12
	Gross	kg	10	10,5	14
Refrigerant			R32	R32	R32
Pipe diameter	Liquid	mm(inch)	6.35(1/4)	6.35(1/4)	6.35(1/4)
	Gas	mm(inch)	9.52(3/8)	9.52(3/8)	12.7(1/2)
	Drain	mm	16,5	16,5	16,5

Note: SENDO reserves the right to change the technical data in the table without prior notice.