

MULTI SPLIT

Indoor units CASSETTE



R32



INVERTER



Wi-Fi
OPTIONAL

Drain pump
integrated



Standard



Optional



NEW

Model	Internal unit		SFM-09CU-AU1	SFM-12CU-AU1	SFM-18CU-AU1
Rated Capacity	Cooling	Btu/h	9560(5120-12115)	12285(5800-12625)	17060(8530-19107)
		kW	2.80(1.50-3.55)	3.60(1.70-3.70)	5.0(2.50-5.6)
	Heating	Btu/h	10240(5640-13000)	13306(6930-15080)	19107(10340-24000)
		kW	3.0(1.60-3.81)	3.9(2.03-4.42)	5.6(3.03-7.03)
Electrical absorption	Power Supply Source	V~, Hz, Ph	220~240, 50, 1	220~240,50,1	220~240,50,1
	Absorption in cooling	W	70(17.5-109)	70(17.5-109)	70(17.5-109)
	Absorption in heating	W	70(17.5-109)	70(17.5-109)	70(17.5-109)
Fan motor	Power	W	30	30	30
	Speed (high / medium / low)	r/min	810/750/660	810/750/660	810/750/660
Performance	Air Flow Volume	m ³ /h	700/353/312	700/600/530	700/600/530
	Sound Pressure Level	dB(A)	45/41/35	45/41/35	45/41/35
	Sound Power	dB(A)	56	56	56
Dimension	Net size (LxPxH)	mm	570x570x260	570x570x260	570x570x260
	Package dimensions (LxPxH)	mm	655x655x295	655x655x295	655x655x295
	Net panel dimensions (LxPxH)	mm	650x650x55	650x650x55	650x650x55
	Panel packaging dimensions (LxPxH)	mm	710x710x80	710x710x80	710x710x80
Weight	Net	kg	18	18	18
	Gross	kg	21	21	21
	Net panel	kg	2,2	2,2	2,2
	Gross panel	kg	3,7	3,7	3,7
Refrigerant			R32	R32	R32
Pipe diameter	Liquid	mm(inch)	6.35 (1/4)	6.35(1/4)	6.35(1/4)
	Gas	mm(inch)	12.7 (1/2)	12.7(1/2)	12.7(1/2)
	Drain	mm	20	20	20