



WWW.SENDO.GR



ZEAS

HIGH THRILLS



R 32



INVERTER



Wi-Fi ready



EXTRA FILTERS



Low operating voltage range 130 ~ 270V



3D air flow

Improves the air distribution and flow, making you feel more comfortable.



Value for money

Best quality / price ratio.

B A S I C M O D E S



Auto defrost



Self-diagnosis of faults



Sleep mode



Turbo mode



Auto restart



Timer



Antibacterial function



Self-cleaning function



Air flow up and down



Follow me mode

| Model | | | | SND - 09 AGN | SND - 12 AGN | SND - 18 AGN | SND - 24 AGN |
|----------------------------|----------------------------|---------------------------|--------------------|-------------------|--------------------|--------------------|--------------------|
| Nameplate parameter | Rated capacity | Cooling | W | 2580 (980 - 2900) | 3500 (1100 - 3700) | 5275 (1200 - 5500) | 7030 (1970 - 7800) |
| | | Heating | W | 2700 (680 - 3000) | 3500 (1100 - 3800) | 5375 (1370 - 6100) | 7050 (2500 - 7600) |
| | Rated power consumption | Cooling | W | 800 (300 - 900) | 1090 (340 - 1150) | 1650 (370 - 2000) | 2200 (600 - 2400) |
| | | Heating | W | 750 (190 - 830) | 970 (300 - 1060) | 1490 (350 - 1700) | 1960 (700 - 2100) |
| | Rated running current | Cooling | A | 3,6 (1,3 - 4,5) | 4,8 (1,5 - 5,4) | 7,3 (1,7 - 9,3) | 10,3 (2,5 - 11) |
| | | Heating | A | 3,4 (0,9 - 4,0) | 4,3 (1,3 - 5,0) | 7,1 (1,6 - 8,0) | 10,5 (2,4 - 10) |
| | Max. input power | | W | 1600 | 1900 | 2900 | 3700 |
| | Max. input current | | A | 8 | 9,5 | 12 | 16 |
| | EER cooling | | W/W | 6,50 / A++ | 6,65 / A++ | 6,57 / A++ | 6,89 / A++ |
| | COP heating | | W/W | 4,37 / A+ | 4,36 / A+ | 4,02 / A+ | 4,11 / A+ |
| | COP heating (warm climate) | | W/W | 5,38 / A+++ | 5,39 / A+++ | 5,40 / A+++ | 5,25 / A+++ |
| | Power supply source | | V / Ph / Hz | 220~240V-1-50Hz | 220~240V-1-50Hz | 220~240V-1-50Hz | 220~240V-1-50Hz |
| | Refrigerant | | | R32 | R32 | R32 | R32 |
| | Refrigerant charged | | g | 580 | 680 | 1280 | 1440 |
| | Air flow volume | | m ³ / h | 600 | 600 | 850 | 1150 |
| Sound power lvl | Outdoor unit | dB (A) | 48 | 50 | 52 | 57 | |
| Indoor unit weight | | Kg | 7,5 | 8 | 12 | 14 | |
| Outdoor unit weight | | Kg | 26 | 26 | 35 | 45 | |
| Piping size | Liquid | mm (inch) | 1/4 | 1/4 | 1/4 | 1/4 | |
| | Gas | mm (inch) | 3/8 | 3/8 | 1/2 | 5/8 | |
| Indoor unit configuration | Dimension | Net dimension (W x D x H) | mm | 750 x 285 x 200 | 750 x 285 x 200 | 900 x 310 x 225 | 1082 x 330 x 233 |
| Outdoor unit configuration | Dimension | Net dimension (W x D x H) | mm | 730 x 545 x 285 | 730 x 545 x 285 | 800 x 545 x 315 | 900 x 700 x 350 |
| Operation temperature | Operating range (cooling) | | °C | 16 - 43 | 16 - 43 | 16 - 43 | 16 - 43 |
| | Operating range (heating) | | °C | -10 - 30 | -10 - 30 | -10 - 30 | -10 - 30 |

The company reserves the right to change the technical characteristics without notice.