



sendo
FEELING COOL



PEGASUS



A+++

PEGASUS

A+++



R 32



INVERTER



Wi-Fi



EXTRA FILTERS



GOLDEN FIN



Low operating voltage range 130 ~ 270V



4D air flow

Balanced airflow with range up to 18m and more precise temperature regulation.



Soundless design

A large compressor in conjunction with the best heat exchange system ensures better cooling performance.

REACHING
FRESHNESS
LEGACY





New model		PEGASUS		9.000 BTU	12.000BTU
Model Code				SND-09PGS/2	SND-12PGS/2
Type				T1, H/P, INVERTER	T1, H/P, INVERTER
Pdesign Cooling	W			2600	3500
Pdesign Heating Average	W			2300	2800
Pdesign Heating Warm	W			2600	3500
SEER	Cooling			8,5	8,5
SCOP	Heatling Average			4,6	4,6
SCOP	Heatling Warm			5,2	5,1
Energy Class	Cooling			A+++	A+++
Energy Class	Heatling Average			A++	A++
Energy Class	Heatling Warm			A+++	A+++
Cooling Capacity	W			2600(800-3200)	3500(1000-4000)
Heating Capacity	W			3000(800-3300)	3900(1000-4400)
Input-Cooling	W			590(170-1400)	890(190-1500)
Input-Heating	W			720(170-1500)	1000(190-1600)
Moisture Removal	L/H.r			0,9	1,2
Air Circulation (Indoor) (H/H-M/M/M-L/L)	m3/h			520/480/450/420/380	580/540/500/470/430
Air Circulation (Outdoor)	m3/h			2000	2200
EER for Cooling	W/W			4,41	3,93
COP for Heating	W/W			4,17	3,90
Max current	A			7,5	8
Refrigerant				R32	R32
Refrigerant charge volume	g			750	800
Indoor Unit Noise Level - Sound Power	dB (A)			56	56
Indoor Unit Noise Level - Sound Pressure	dB (A)			39/37/35/33/31/26	40/38/36/34/31/26
Outdoor Unit Noise Level - Sound Power	dB (A)			61	62
Outdoor Unit Noise Level - Sound Pressure	dB (A)			53	54
Annual energy consumption(heating)	Annual energy consumption(cooling)			107	144
	warmer			700	961
	average			700	852
	colder			/	/
Voltage, Frequency, Phase				220-240V~,50Hz,1P	220-240V~,50Hz,1P
Rated Current	Cooling (A)			2,6	4
	Heating (A)			3,2	4,5
Compressor MFG				GMCC	GMCC
Liquid Pipe	inch			1/4	1/4
Gas Pipe	inch			3/8	3/8
Fire Alarm/Room Card Port				Yes	Yes
HEPA Filter				Yes	Yes
Wifi APP Control				Yes	Yes
Voice Control (with Alexa Google)				Yes	Yes
3 Speed and Auto Indoor Fan Control				Yes	Yes
Vertical Auto Swing Louver				Yes	Yes
Sleep Operation				Yes	Yes
Smart Function				Yes	Yes
Auto Restart				Yes	Yes
Silent Mode				Yes	Yes
Dimmer				Yes	Yes
2 Ways Draining Connection (Left or Right)				Yes	Yes
Low ambient temperature cooling				Yes	Yes
Horizontal Auto Swing Louver				Yes	Yes
Net Dimensions WxHxD (mm)	Indoor Unit			790×255×203	790×255×203
	Outdoor Unit			780×540×260	810x585x280
Net Weight (Kg)	Indoor Unit			7.7	7.8
	Outdoor Unit			28	33
Packing Dimensions WxHxD (mm)	Indoor Unit			850×320×260	850×320×260
	Outdoor Unit			910×600×360	940×630×385
Gross Weight (Kg)	Indoor Unit			9.5	9.5
	Outdoor Unit			31,5	37
Test Standard				EN 14511,EN 14825, EN 12102	EN 14511,EN 14825, EN 12102
Approvals				CE	
Operating Temp Range (°C)	cooling			-15°C-43°C	-15°C-43°C
	heating			-20°C-24°C	-20°C-24°C
Max allowable tubing length at shipment	m			5	5
limit of tubing length	m			15	15
limit of elevation difference H	m			8	8
required amount of additional refrigerant	g/m			20	20